



Soft Touch™

MODEL 572A-40

DEEP ACCESS- LONG REACH

THERMOSONIC WIRE AND RIBBON BONDER

0.5 to 2.0 mil (12.7 to 50 μm) diameter wire and up to 1 x 10 mil (25.4 x 254 μm) ribbon



STANDARD FEATURES:

- HYBOND *Soft Touch™* energy system.
- Front panel ultrasonic test button.
- Deep vertical access of 0.53 in. (1,34cm).
- Long horizontal reach of 6.5 in. (16,5cm).
- 0.5 inch and 2 inch spool mounts standard.
- Loop height control adjustment.
- Motorized vertical wire feed.
- 1-1-2; 1-2-2 and 1-2-1 stitch capability.
- Swing away clamps for easier wire threading.
- Deep access wire-in-tool 90° wire feed.
- Variable angle microscope mount.
- Audio and visual bond fault indicators.
- Independent 1st and 2nd bond controls.
- Front panel feed switch for manual tail adjust.
- 10 x 12 in. (25,4cm x 30,3cm) X-Y work platform.
- LED display for monitoring temperature.
- Independent lever for Z bond head control.
- Wire and ribbon bonding capability.

Imitated but never duplicated, HYBOND's exclusive *Soft Touch™* force ramping system bonds effectively with less trauma to sensitive materials like GaAs and InP. Superior wire control is provided by the motorized feed system which features clamps capable of feeding wire and ribbon, dial adjustable tail length, switch for manual tail length adjustment and clamp pull back dial adjustment to allow bonding and cutting of softer (higher elongation) wires than conventionally used for wedge bonding. Model 572A-40 includes front panel independent controls for 1st and 2nd bond U/S, Time & Force as well as for the built in work stage temperature controller. The 572A-40 has a proven track record of safe and effective wire and ribbon bonding worldwide.

Partial List of Available Options:

- **OP-06S6:** Leica S6 Zoom Stereo Microscope.
- **OP-06A:** Nikon SMZ660 Microscope.
- **OP-08A:** Dual Fiber Optic Illuminator.
- **OP-08R-LED:** White LED Ring Illuminator.
- **OP-12:** 240VAC 50/60Hz Input Wiring.
- **OP-17:** Motorized de-spooler.
- **OP-30A:** 8:1 X-Y Manipulator.
- **OP-31:** Tool Heater and Temp. Controller.
- **OP-44:** High/Low U/S Power Selector.
- **OP-84:** Heated Transducer for Tool Heat.
- **WST-15A:** Heated Work Stage, 2.125 in. top.
- **WST-19A:** Heated Work Stage, 4 x 6 in. top.
- **WST-65:** Heated Work Stage, 10 x 6 in top.
- **Wire & Wedge Tool** as ordered per application.

Model 572A-40 Specifications:

- Ultrasonic (U/S) System: PLL self tuning 62.5KHz (nominal) system (± 2.5 KHz).
- U/S Power Range: 0-1 watt on low setting (default) and 0-2 watts on high setting.
- Bond Time Range: 10mSec. to 400mSec.
- Bond Force Range: 15gr. to 120gr.
- Temperature Control Range: Ambient to 250 degrees Celsius.
- Bondable Wire Diameters: 0.5 to 2.0mil (12,7 to 50 μ m) diameter.
- Bondable Ribbon Dimensions: Up to 1 x 10mil (25,4 x 254 μ m).
- Bondable Wire/Ribbon Materials: Gold and aluminum.
- Bond Head Movement: Manual.
- Bond Actuation: Switch at fixed height. Activated by lever.
- Z Travel/Vertical Bonding Window: 0.5in. (1,27cm)/60-100mils (152-254 μ m).
- Table Motion: 4:1, manual.
- Input Power Requirements: 110VAC 50/60Hz @ 10A max. **240VAC with OP-12.**
- Minimum Bench Space Required: Width: 25in., Depth: 30in. (63,5x76,2cm).
- Unit Weight/Shipping Weight: 70 lbs. (31,8Kg)/150 lbs. (68,2Kg). Shipping weight may vary.
- Industry Standards: CE.

For more information contact us:



330 State Place, Escondido, CA. 92029, USA

Tel. 760-746-7105 Fax. 760-746-1408

e-mail: mailus@hybond.com or visit us online at: www.hybond.com